

M K 5 0 0 G S MINIKEY ACCESS CONTROL SYSTEM

Self-Contained Keypad System for Door and Gated Entrances.



KEY FEATURE

STAND-ALONE ACCESS SYSTEM

Compact for easy installation

SMART

GREATER CONTROL AT THE SITE WITH TWO RELAYS THAT CAN BE CONTROLLED INDIVIDUALLY OR TOGETHER.

INCREASED CONVENIENCE WITH CODES THAT CAN BE PROGRAMMED USING 4 OR 5 DIGITS AND ACTIVATE ONE OR BOTH RELAYS.

STORES DATABASE INFORMATION IN MEMORY WHEN THE POWER GOES OUT, ENSURING IMMEDIATE STARTUP AND OPERATION WHEN POWER IS RESTORED.

RELIABLE

ENGINEERED TO BE WEATHER-RESISTANT AND HIGHLY VANDAL-RESISTANT WITH A WELL-CRAFTED LOOK FOR INTERIOR OR EXTERIOR USE.

EXCELLENT VISIBILITY DAY OR NIGHT WITH RECESSED SIDE-LIT METAL KEYPAD.

SECURE

PREVENTS UNAUTHORIZED ENTRY BY DISABLING KEYPAD FOR 3 MINUTES IF AN UNAUTHORIZED USER HAS ATTEMPTED TOO MANY INCORRECT ENTRY CODES. THE SYSTEM CAN BE PROGRAMMED TO PERMIT FROM 1 TO 10 ATTEMPTS PRIOR TO ENGAGING THE LOCKOUT.

TOTAL SOLUTION ACCESSORIES:

GOOSENECK PEDESTAL

42 in. pad mount or 64 in. in-ground pedestal 2x2 in. square pipe, black powdered coat finish 11 ga. Steel.



PED42 / PED64

LIFTMASTER ELITE SERIES®

Maglock 12/24VDC with Junction Box features 1,300 lbs. holding force.



MG1300

MASTERFUL ENGINEERING.

CAPABILITIES



- 500 Entry Codes
- Variable Entry Code Length – can be programmed using 4 or 5 digits and can activate a single relay or both relays.
- Two Relays, one for the main unit and one auxiliary relay to support status inputs up to 500 feet from the main unit.
- Relays can be controlled individually or together.
- Programmable Relay Times – each relay may be programmed independently to activate from 2 to 255 seconds.
- Time Clock Input feature makes it possible to use a dealer-supplied time clock to prevent entry to the facility at a specified time.
- Lightning Protection – inputs and power connections contain some protection against typical voltage spikes. However, in an area where lightning is prevalent, external surge suppressors should be used to minimize damage to the system.

POWER



- 12VAC or 13.5VDC



3.5"

4.5"

4.5"

MECHANICS



- Grained Stainless Steel - Surface Mount

DIMENSIONS



- Surface Mount:
4.5" W x 4.5" H x 3.5" D

STANDARD SPECS.

WARRANTY

- 1-Year Limited

RELAYS

- (1) Main Unit
- (1) Auxiliary

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTON (1)

- 12.25" W x 11.12" H x 7.5" D
- Keypad System
- Power Supply
- Instruction Manual

For Support Tools and Training Videos, Visit
LiftMasterTraining.com

For More Information, Visit
LiftMaster.com/AccessControl

Sales Support: **800.282.6225**
Technical Support Center: **800.528.2806**
LiftMasterDealer.CustHelp.com/App/Ask